

HENKE WINGS FOR DEERE GRADERS



*From flatlands to mountain tops and everywhere in between,
Henke has a wing designed for your application.*

888.682.9010
henkemfg.com

HENKE®



HENKE STANDARD ALL HYDRAULIC WING

66" POST AND 42" POST (AHW)

Engineered to perform.
Built to endure.

Tall Post (66") for maximum benching height

Henke's traditional wings give you superior benching control and smooth-lift performance.



Short Post (42") for good visibility

Key Benefits



NYLATRON SLIDE GUIDES
protect slide assembly.



UNIQUE MUDROC hydraulic relief valve limits excessive down pressure and prevents mechanical binding and damage to the moldboard cylinder when the grader articulates.



HEAVY DUTY BOX PANEL REINFORCED MOLDBOARD
built to withstand even the toughest conditions, while preventing torsional twist.



Unique post design allows
WING-SIDE CAB DOOR ACCESS (on most models).



Standard 1/2" x 8" SAE 1084
HIGH CARBON STEEL CUTTING EDGE.



HENKE'S BOLT-UP DESIGN
makes it easy to remove wing post for summer use and to perform maintenance when needed.

HENKE WINGS COMPLETE YOUR SNOW-FIGHTING PACKAGE

Standard AHW Features/Components

- Leading end height 28" and discharge end height 38"
- 3/16" thick high tensile steel rolled plate, box paneled design moldboard
- Telescoping, spring cushioned pushbar
- 24" – 28" high benching post assembly of 5/16" high-tensile steel
- Bolt-up design allows post to be unbolted from belly plate (to remove wing post for summer use)
- Unique MUDROC (Make-Up-Dual-Relief-Over-Center) hydraulic relief valve is a standard feature, and prevents mechanical binding that could occur when machine articulates, and provides for limited wing down pressure
- Hose kit to connect Henke wing cylinders to grader valves
- ½" x 8" SAE 1084 high carbon steel cutting edge (standard)
- Elevating, Fixed and RearRipper models available



Contact us about
Factory Installation

Learn more at:

<http://henkemfg.com/grader-wings-standard/>

HENKE®

888.682.9010
henkemfg.com



HENKE POSTLESS HYDRAULIC WING (PLHW)

Engineered for
maximum visibility
and control.

Henke's postless wing is designed
for safety while allowing for easy
installation and removal.



Key Benefits



HEAVY DUTY BOX PANEL REINFORCED MOLDBOARD

built to withstand even the
toughest conditions, while
preventing torsional twist.




SPRING CUSHIONED PUSH BEAM

with shear bolt to
absorb shock loads due to
impact reducing stresses on
your machine.



Design allows for **6" OF
MECHANICAL FLOAT** and
approximately 24" - 26"
benching height*

(*depends on tire height)



UNIQUE MUDROC hydraulic
relief valve limits excessive
down pressure and prevents
mechanical binding and damage
to the moldboard cylinder when
the grader articulates.



Standard 1/2" x 8" SAE 1084
**HIGH CARBON STEEL
CUTTING EDGE.**



**HENKE'S 3" BANJO PIN IS
THE BEST IN THE INDUSTRY**
Henke's products are designed
to withstand heavy workloads.

INCREASE THE POWER

CLEAR ROADS MORE EFFECTIVELY WITH A HENKE WING

Henke PLHW Standard Features/Components

- Leading end height 28" and discharge end height 38"
- 3/16" thick high tensile steel rolled plate, box paneled design moldboard
- Telescoping, spring cushioned pushbar
- 24" – 28" high benching post assembly of 5/16" high-tensile steel
- 3" banjo pin is designed to withstand heavy workloads (to remove wing post for summer use)
- Unique MUDROC (Make-Up-Dual-Relief-Over-Center) hydraulic relief valve is a standard feature, and prevents mechanical binding that could occur when machine articulates, and provides for limited wing down pressure
- Hose kit to connect Henke wing cylinders to grader valves
- 1/2" x 8" SAE 1084 high carbon steel cutting edge (standard)
- Elevating, Fixed and RearRipper models available



Learn more:
<http://henkemfg.com/grader-wing-postless/>

HENKE®

888.682.9010
henkemfg.com

HENKE SNOW PLOWS FOR DEERE GRADERS

Henke offers a wide range of front snow plows. Contact us for help selecting the best plow for your application.



REVERSIBLE END LOADER PLOW (REL)

The most ruggedly built, full-tripping, power-reversing plow on the market. The Henke REL is a heavy duty reversible snow plow for motor graders and wheel loaders.

- Full trip moldboard
- Accepts hydraulic down pressure to break up packed snow and ice
- Compatible with these lift groups: Parallel (Balderson Style), AQC Parallel and Scarifier (see page 10)
- One-piece 50,000 PSI high tensile steel pushframe is the strongest and most durable in the industry

HENKE HIGH PERFORMANCE OPTIONS:

Add a Mechanical Float or Swivel Backplate to handle rugged situations and uneven surfaces.



Add a Henke Hi-Gate to your REL plow for optimal snow control when you need it.

Learn more at:

<http://henkemfg.com/higate/>

TRUCK PLOWS FOR GRADERS

Most of Henke's truck plows can be adapted for use with your Grader, just add an adapter and you're ready to go!

Straight Plows

Expressway Plows

Funnel Plows

Airport Plows

Learn more at:

<http://henkemfg.com/front-snow-plows-for-graders/>

HENKE®

888.682.9010
henkemfg.com

HENKE V PLOWS FOR DEERE GRADERS



***HENKE's attachment solutions
integrate seamlessly with
DEERE graders.***

***When the snow gets deep and keeps
on coming, Henke answers the call
with our rugged, dependable line of
V-Plows. These monsters tackle the
heaviest accumulation and drifting with
unmatched performance.***

FOLDING V PLOW

The Henke Folding V-Plow is a heavy duty, multi-directional dozer blade for wheel loaders and motor graders. It is designed to accept machine downpressure from wheel loader arms or Henke motor grader parallel lift groups, and is ideal for light dozing, grading and snow removal.

HENKE HIGH PERFORMANCE OPTIONS:

***Add a Mechanical Float or Swivel Backplate
to handle rugged situations and uneven surfaces.***

V-10 FIXED PLOW

This time-tested Henke product that can be seen in use across the globe. The V-10's unique blade curvature helps bust through drifts and deep snow to open roads.

HENKE OFFERS YOU THE BEST IN V PLOWS

Learn more at:

<http://henkemfg.com/v-plows/>

HENKE®

888.682.9010
henkemfg.com

HENKE DOZER BLADES FOR DEERE GRADERS

***HENKE's attachment solutions
integrate seamlessly with
DEERE graders.***

***Henke Dozer Blades are great tools for
general purpose plowing and grading,
and can be mounted on motor graders,
industrial loaders and trucks.***

STANDARD DUTY DOZER BLADES (DB)

The DB Dozer Blade can be used on a grader or loader, in summer as well as winter, enabling you to get maximum versatility from both machine and attachment.

SEVERE DOZER BLADES (SDDB)

The Henke Severe Duty Dozer Blade is a heavy-duty, high-curvature, box-panel reinforced dozer-blade for use on motor graders and wheel loaders. The extra heavy-duty construction allows operators to take an aggressive approach to snow removal.

HENKE HIGH PERFORMANCE OPTIONS:

***Add a Mechanical Float or Swivel Backplate
to handle rugged situations and uneven surfaces.***

HENKE OFFERS YOU MORE TO CHOOSE FROM

We also have down-pressure, dual-power, reverse utility dozer blades sized for your application.



Learn more at:

<http://henkemfg.com/dozer-blades/>

HENKE®

888.682.9010

henkemfg.com

HENKE HIGH PERFORMANCE OPTIONS



Swivel Back Plate for following the crown of the road



Mechanical Float Link for following the contours of the road



Sight Gauge for ease of use and optimal performance

Add our exclusive Mechanical Float and/or a Swivel Back Plate and you'll have the best performance available.

SWIVEL BACK PLATE

Henke's Swivel Back Plate enables the plow to follow the crown of the road giving it the flexibility to float side to side.

HENKE MECHANICAL FLOAT LINK

This feature allows the plow to "float" up and down over uneven terrain, following the contours of the road. Mechanical Float adds an additional 10" -12" of vertical travel to the plow. The Sight Gauge makes it easy to set the plow in proper position (pushframe parallel to the ground) for highly effective plow performance.

Combine the Mechanical Float Link with the Swivel Back Plate and you'll have the highest performing plow available.

BOTH OPTIONS ARE AVAILABLE ON THESE HENKE PRODUCTS:

Reversible End Loader Plow (REL); Folding-V Plow;
Severe Duty Dozer Blade (SDDB); Henke Helper

Click on the image below to see a short video about the REL plow with Swivel Back Plate and Mechanical Float Link



888.682.9010
henkemfg.com

HENKE®

HENKE HI-GATE FOR DEERE GRADERS

***HENKE's attachment solutions
integrate seamlessly with
DEERE graders.***



***The Hi-Gate lets you drag and drop snow
where you want on the first pass.***

HENKE HI-GATE

The Henke Hi-Gate brand is a superior performing snow gate. Field tested and proven, Henke's hi-Gate receives high marks from Fleet Managers across the Nation.

Features

- A spring cushioned road contact strip will be provided with a rubber cutting edge to allow for grader moldboard actuation and continuous down pressure.
- Gate and cylinder are easily removed in minutes.
- Allows for moldboard rotation.
- Structural reinforcements throughout to prevent bending.
- US Patent# 6,347,465 & 7100314

"We tested two different type of snow gates during this three year process, and the Henke snow gates performed the best. They allowed us to get to the curb the closest, they were engineered so they fit our moldboard better, and it allowed us to clean the gutter-pan better than with the other snow gate."

Gaylnn Huber, Street/Fleet Manager at City of Sioux Falls, SD

HENKE®

888.682.9010
henkemfg.com

Learn more at:

<http://henkemfg.com/higate/>

HENKE OPTIONS – TAKE YOUR ATTACHMENTS TO ANOTHER LEVEL

HENKE LIFT GROUPS FOR DEERE MOTOR GRADERS



**PARALLEL
LIFT GROUP**



**AQC
LIFT GROUP**



**SCARIFIER
TOOL BAR**

Henke offers several lift systems built to connect front plows to motor graders for severe duty applications.

Features

- Compact design brings weight of implement closer to grader, resulting in less impact on the front axle.
- Integrated mechanical stops prevent overloading of cylinder.
- Fully greasable cold-rolled, zinc-plated, steel pin assemblies at all joints
- 36" of overall vertical lift
- Drift lock pin prevents accidental load drift during transport
- Upper lift arms are 1.5" thick, with horizontal connecting plates for extra strength
- Lower lift arm assembly includes (4) 1" thick ears on each end, joined by (2) 6x4x1/2" structural tubes
- Severe duty 4" bore lift cylinder, with nitrided rod and 1.5" diameter trunnions, provides 36" of overall vertical lift



Learn more about
our lift groups at:
[http://henkemfg.com/
parallel-lift-groups-
graders/](http://henkemfg.com/parallel-lift-groups-graders/)

HENKE, Engineered to give you the best.

A CULTURE BUILT WITH THE CUSTOMER IN MIND

We start by **listening** to our customers and to understand each unique challenge that is being faced in each specific setting. Then our field consultants and engineers use their expertise to design a solution to meet the need rugged and resilient products.

FUTURE FOCUSED

The future is being built today, HENKE is constantly updating and **improving** our manufacturing facility to deliver quality and be responsive to our customers' needs. We evaluated the long term performance of our products and look for ways to make them easier to use, more versatile and longer lasting.

A DEDICATED TEAM THAT DELIVERS

When you call on HENKE, you will receive first rate service backed by a team of seasoned industry professionals. With HENKE, your concern is our concern and we will give everything we have to create a successful outcome for you.

Learn more at:

<http://henkemfg.com>



888.682.9010
henkemfg.com

